

PELLETIZING & PULVERIZING SYSTEMS

Pulverizer REX basic Xtremly simple operation

CD REDUCTION

The REX basic Pulverizer was designed for users that do not require tight particle distribution specification and can be used to pulverize a wide variety of materials. This includes compounding, extrusion, molding and recycling markets. To further enhance the process capabilities, several different process cooling innovations can be added to the machine. Some Engineered Polymers require extremely low temperatures to enable processing. These cooling options make this unit a viable alternative to a full cryogenic pulverizer.

Advantages

- Wide field of applications
- Heavy-duty construction
- Special cooling systems for Engineered Polymers
- Versatile and space-saving configurations
- Different disc configurations to increase output

Pulverizer REX basic **x**tremly simple operation





Blower, Cyclone and Transfer System

Mill Chamber and Manual Controls

Technical data:		REX basic	REX basic PLUS
Material:		LDPE, HDPE, PVC, ABS, ¹⁾	
Feed size:	mm	≤ 10.0	
Final Fineness:	μm	approx. 800-1,000	
Output:	kg/h	250 - 700	700 - 2,000
Discs:	No./Diameter (mm)	2 / 432	
Main Drive:	kW	22	55
Controls:	Siemens	manual	
Dimensions:	L x W x H (mm)	3,818 x 3,701 x 4,163	

1) further materials upon request



